

Liquid-Applied Flashings in Warranted Elevate Roofing Systems

**To: Elevate Applicators
Elevate Distributors
Elevate Sales Representatives**

April 2026

Dear Valued Customer,

Elevate is committed to providing our customers with high-quality, comprehensive product offerings for use in warranted Elevate roofing systems. As part of this ongoing effort, we are introducing several updates to our liquid-applied flashing solutions to support greater flexibility and application consistency in the field.

Please review the following updates:

1. New Liquid-Applied Flashings Application Guide:

The new [Elevate Liquid-Applied Flashings Application Guide](#) is now available to address all liquid flashing applications in conjunction with warranted Elevate roofing systems. This guide has replaced the One-Part Pourable Sealer Flashing Guide and the UltraFlash™ Liquid Flashing Guide.

2. MAX™ PVC and AC Fast FR:

Elevate will now allow the use of AC Fast FR in qualifying warranted Elevate MAX PVC roofing systems. AC Fast FR will provide a liquid-applied alternative to pre-molded or field-fabricated PVC flashings in combination with new MAX PVC roof systems. The following details are provided for reference:

Thermoplastic Details – Now Applicable to MAX PVC Roofing Systems	
New Detail Number	New Detail Name
TPM-S-08	Thru-Wall Scupper (MAX PVC) with Elevate AC Fast FR Membrane Liquid Flashing
TPM-T-29	Elevate Termination Bar at Tilt Up Panel Joint (MAX PVC) Flashed with Liquid Flashing
TPM-BT-01B	Base Tie-In with HD or HD Plus Plate at Deck – Liquid Flashing (MAX PVC)
TPM-P-25	Penetration with Liquid Flashing (MAX PVC)
TPM-P-27	I-Beam Penetration with Liquid Flashing (MAX PVC)
TPM-RE-29	Roof Edge with Liquid Flashing (MAX PVC)

NOTES:

- **Contractors not familiar with AC Fast FR must request a job-start up inspection through PIN prior to use on all membrane roofing systems.**

- Contractors should reach out to local sales representatives for availability and pricing.
- AC Fast Primer is not required where directly applied to MAX PVC membrane.
- AC Fast FR applications are approved for new and aged MAX PVC membranes. In-service membranes must be cleaned and wiped with Elevate P-100 cleaner. Refer to the new Liquid-Applied Flashings Application Guide for more information.

3. UltraFlash™ One-Part Liquid Flashing Update:

For 20-Year Red Shield Warranties, the application requirements remain unchanged: a 90 mil, 3-course system with UltraFlash Fabric reinforcement.

Following the discontinuation of UltraFlash Two-Part Liquid Flashing for 25-Year and 30-Year Red Shield Warranties, it is now acceptable to apply an additional 30-mil finish coat instead of the 5-course application on qualifying SBS and APP roofing systems. Please note, roof granules are required to broadcast into the fresh (wet) compound, which should match the surrounding roof surface.

For more information, please refer to the Elevate Application and Design Guides, applicable Technical Information Sheets, and Details available on [our website](#) or contact your Elevate Regional Technical Coordinator at 800-428-4511.

Sincerely,



Jackie LaDuke
National Technical Manager
Thermoplastic Systems



Victor Rosenthal
National Technical Manager
Asphalt & EPDM Systems